

**Canon**



**imageRUNNER**  
ADVANCE

**C5051 / C5045**  
**C5035 / C5030**

multifunction printer  
compact design  
color/black and white

**OFFICE SOLUTIONS**




advancing business





# imageRUNNER ADVANCE



**C5051**  
**C5045**  
**C5035**  
**C5030**

 Copy/Print/Send/Fax/Store

 Up to 12" x 18"

 1200 x 1200 dpi

 Color

#### Exceptional power

- > Advanced imageCHIP system architecture
- > 80GB HDD standard; up to 250GB HDD
- > 2GB RAM standard, 2.5GB RAM maximum

#### Impressive speed

- > Up to 51-/45-/35-/30-ppm printing (BW, Color; Letter)
- > Up to 100-ipm single-pass duplex scanning at 300 dpi (BW, Color)\*

#### Outstanding paper handling

- > Up to 5,000-sheet maximum paper capacity
- > 14 lb. Bond to 140 lb. Index
- > Plain, heavy, coated, tabs, envelopes

#### Flexible in-line finishing options

- > Multiposition stapling, 2- and 3-hole punching, booklet-making
- > Internal finisher with 50-sheet stapling

#### Enhanced collaboration

- > Advanced Box document sharing solution
- > Standard Universal Send
- > Adobe® PDF formats
- > Scan/print via USB

#### imageRUNNER ADVANCE Essentials

- > imageRUNNER ADVANCE Desktop
- > imageRUNNER ADVANCE Tracker
- > Workflow Composer and Connectors

#### Strong environmental focus

- > ENERGY STAR® qualified
- > Reduction of CO<sub>2</sub> emissions in manufacturing process
- > Exceeds EU RoHS Directive standards

\* imageRUNNER ADVANCE C5051/C5045 models

An extensive range of optional accessories to advance your business.

**Finishing Options**



**Inner Finisher-A1**

- 500-sheet capacity\*
- Corner and double stapling up to 50 sheets


**Staple Finisher-C1**



- 2-tray, 3,000-sheet capacity
- Corner and double stapling up to 50 sheets

**Booklet Finisher-C1**

- 2-tray, 3,000-sheet capacity
- Corner and double stapling up to 50 sheets
- Booklet-making up to 16 sheets



**External 2/3-Hole Puncher-B1\*\***

- 2- and 3-hole punching

**Other Output Options**

- Inner 2-way Tray-F1**
- Copy Tray-J1**
- Inner Finisher Additional Tray-A1**



**Printer Options\*\*\***

**PCL Printer Kit-AE1**

**PS Printer Kit-AE1**

**Direct Print Kit (for PDF/XPS)-H1**

**imagePASS-B1**

- Intel® Celeron® M440 1.88GHz Processor
- 512MB RAM, expandable to 1GB
- 80GB Hard Disk
- Adobe PS 3/PCL 5c/PCL 6

**ColorPASS-GX300†**



- Intel® Core™2 Duo Xeon E8400 2 x 3.0GHz Processor
- 2GB RAM standard
- 160GB Hard Disk
- Adobe PS 3

**Accessibility Options**

**Remote Operator's Software Kit-B1**

**Voice Operation Kit-C1**

**Voice Guidance Kit-F1**

**Braille Label Kit**

**ADF Access Handle-A1**



**Paper Feeding Options**

**Cassette Feeding Unit-AD1**

- 550-sheet x 2-cassette capacity
- 14 lb. Bond to 110 lb. Index
- Supports up to 12" x 18"

**Other Paper Feeding Options**

**Envelope Feeder Attachment-D1**

- 50-sheet capacity
- Supports COM10 No.10, Monarch, DL, ISO-B5,ISO-C5

**Tab Feeding Attachment Kit-B1**

**Cabinet Type-B**

**Paper Deck Unit-B1**

- 2,700-sheet capacity
- 14 lb. Bond to 28 lb. Bond
- Supports letter-sized paper



**Security Options**

**Universal Send Security Feature Set-D1**

**Universal Send Digital User Signature Kit-C1**

**Encrypted Secure Print-D1**

**Secure Watermark-B1**

**Document Scan Lock Kit-A1**

**Data Erase Kit-C1**

**HDD Data Encryption and Mirroring Kit-C1**

**Removable HDD Kit-AC1**

**IPSec Board-B2**

\*300-sheet capacity when Additional Tray-A1 is attached.

\*\*External 2/3-Hole Puncher-B1 can only be installed with either the Staple Finisher-C1 or Booklet Finisher-C1.

\*\*\*UFR II standard.

†Available on imageRUNNER ADVANCE C5051 only.

# Product Specifications

## Main Unit

<b>Operation Panel</b>	
8.4" SVGA Full-color TFT Screen	
<b>Memory</b>	
Standard:	2GB RAM
Maximum:	2.5GB RAM
<b>Hard Disk Drive</b>	
Standard:	80GB
Maximum:	250GB
<b>Network Interface Connection</b>	
Standard:	10/100/1000Base-TX
Optional:	Wireless LAN (IEEE 802.1x)
<b>Other Interface</b>	
Standard:	USB 2.0 (Host)x2, USB 2.0 (Device)
Optional:	Device Port [USB 2.0 (Host)x2], Serial Interface, Copy Control Interface
<b>Copy/Print Speed (BW/Color)</b>	
Letter:	<b>C5051:</b> Up to 51/51 ppm <b>C5045:</b> Up to 45/45 ppm <b>C5035:</b> Up to 35/35 ppm <b>C5030:</b> Up to 30/30 ppm
<b>First-Copy-Out Time (Letter)</b>	
<b>C5051/C5045:</b>	BW: 4.0 Seconds Color: 6.5 Seconds
<b>C5035/C5030:</b>	BW: 5.5 Seconds Color: 8.9 Seconds
<b>Paper Sources (20 lb. Bond)</b>	
Standard:	Dual 550-sheet Paper Cassettes 100-sheet Stack Bypass
Maximum:	5,000 Sheets
<b>Output Paper Capacity (20 lb. Bond)</b>	
Standard:	250 Sheets (Inner Tray)
Maximum:	3,100 Sheets (with Staple Finisher or Booklet Finisher)
<b>Output Paper Sizes</b>	
Cassettes:	12"x18",* 11"x17",* Legal, Letter, Letter-R, Statement-R, Executive, Custom Size (5-1/2" x 7-1/8" to 12" x 18")
Bypass:	12"x18", 11"x17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18")
<b>Acceptable Paper Weights</b>	
Cassettes:	14 lb. Bond to 110 lb. Index (52 to 209g/m <sup>2</sup> )
Bypass:	14 lb. Bond to 140 lb. Index (52 to 256g/m <sup>2</sup> )
<b>Warm-up Time</b>	
38 Seconds from Power On	
<b>Power Requirements/Plug</b>	
<b>C5051/C5045:</b>	120V AC, 60Hz, 20A/NEMA 5-20P
<b>C5035/C5030:</b>	120V AC, 60Hz, 15A/NEMA 5-15P

<b>Dimensions (H x W x D)</b>	
<b>C5051/C5045:</b>	38-5/8" x 24-3/8" x 29-7/8" (982mm x 620mm x 760mm)
<b>C5035/C5030:</b>	37" x 24-3/8" x 29" (938mm x 620mm x 735mm)
<b>Installation Space (W x D)</b>	
<b>C5051/C5045:</b>	42-1/8" x 52" (1071mm x 1319mm)
<b>C5035/C5030:</b>	42-1/8" x 49-5/8" (1071mm x 1259mm) (when Stack Bypass is extended)
<b>Weight</b>	
<b>C5051/C5045:</b>	Approx. 379 lb.**
<b>C5035/C5030:</b>	Approx. 342 lb.**
<b>Toner (Estimated Yield @ 5% Coverage)</b>	
<b>C5051/C5045</b>	
Black:	44,000 Images
Color (C,M,Y):	38,000 Images
<b>C5035/C5030</b>	
Black:	36,000 Images
Color (C,M,Y):	27,000 Images

## Image Reader Unit

<b>Scan Resolution</b>	
Up to 600 x 600 dpi	
<b>Acceptable Originals</b>	
Sheet, Book, 3-Dimensional Objects [up to 4.4 lb. (2kg)]	
<b>Maximum Original Size</b>	
Up to 11" x 17"	
<b>Document Feeder</b>	
<b>Scan Method (Standard)</b>	
<b>C5051/C5045</b>	Single-pass Duplexing Automatic Document Feeder
<b>C5035/C5030</b>	Duplex Automatic Document Feeder
<b>Acceptable Originals</b>	
Paper Size:	11" x 17", Legal, Letter, Letter-R, Statement, or Statement-R
<b>Scan Speed (BW/Color; Letter)</b>	
<b>C5051/C5045</b>	
Simplex:	Up to 70/70 ipm (300 dpi)/ Up to 70/51 ipm (600 dpi)
Duplex:	Up to 100/100 ipm (300 dpi)/ Up to 70/51 ipm (600 dpi)
<b>C5035/C5030</b>	
Simplex:	Up to 46/46 ipm (300 dpi)/ Up to 46/46 ipm (600 dpi)
Duplex:	Up to 17.5/17.5 ipm (300 dpi)/ Up to 17.5/17.5 ipm (600 dpi)
<b>Paper Capacity (20 lb. Bond)</b>	
<b>C5051/C5045:</b>	150 Sheets
<b>C5035/C5030:</b>	100 Sheets

## Print Specifications

<b>Engine Resolution</b>	
1200 x 1200 dpi	
<b>PDL Support</b>	
Standard:	UFR II
Optional:	PCL 5c, PCL 6, Adobe PS 3
<b>Print Driver Supported OS</b>	
UFR II,	Windows* (Windows 2000/XP/Server 2003/Server 2008/Windows Vista*/Windows 7), Citrix MetaFrame, Macintosh* (OS X 10.4.9 or later)
Adobe PS 3:	Windows (Windows 2000/XP/Server 2003/Server 2008/Windows Vista/Windows 7), Citrix MetaFrame
PCL 5c/6:	Windows (Windows 2000/XP/Server 2003/Server 2008/Windows Vista/Windows 7), Citrix MetaFrame
XPS:	Windows Vista, Windows Server 2008, Windows 7
<b>Direct Print Support</b>	
Standard:	TIFF, JPEG, EPS***
Optional:	PDF, XPS***

## Universal Send Specifications

<b>Sending Method</b>	
E-mail, I-Fax, File Server (FTP, SMB, WebDAV), User Inbox, Super G3 Fax (Opt.)	
<b>Communication Protocol</b>	
File:	FTP (TCP/IP), SMB (TCP/IP), WebDAV
E-mail/I-Fax:	SMTP, POP3, I-FAX (Simple, Full)
<b>File Format</b>	
Standard:	TIFF, JPEG, PDF, PDF (Compact), PDF (Apply Policy), PDF (Optimize for Web), PDF/A-1b, XPS, XPS (Compact)
Optional:	PDF (Trace & Smooth), PDF/XPS (OCR), PDF (Encrypted), PDF/XPS (Digital Signature), PDF (Reader Extensions), Office Open XML (OCR)
<b>Fax Specifications</b>	
<b>Maximum Number of Connection Lines</b>	
4	
<b>Modem Speed</b>	
Super G3:	33.6 Kbps
G3:	14.4 Kbps
<b>Compression Method</b>	
MH, MR, MMR, JBIG	
<b>Sending/Recording Size</b>	
Statement to 11" x 17"	

## Store Specifications

<b>Mail Box (Number Supported)</b>	
100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes	
<b>Advanced Box</b>	
Available Disk Space:	Approx. 10GB (Standard HDD), 115GB (250GB HDD)
Communication Protocol:	SMB or WebDAV
Supported Client PC:	Windows (Windows 2000/XP/Windows Vista)
<b>Memory Media</b>	
Standard:	USB Memory
Optional:	SD, SDHC, CompactFlash, Memory Stick, Microdrive

## Security Specifications

**Standard**  
 Department ID Management, Single Sign-On H, Access Management System (Device and Function Level Log-in), Secure Print, Trusted Platform Module, User Access Control of Advanced Box, Mail Box Password Protection, IPV6, Restricting Features (Restricting the Send Function, Restricting New Addresses on Address Book), SSL Encrypted Communication, SNMPv1/v3, MAC/IP Address Filtering, SMTP Authentication, POP Authentication before SMTP, HDD Format, Adobe LiveCycle Rights Management ES2 Integration

## Other Optional Accessories

- Utility Tray-A1
- USB Keyboard
- Key Switch Unit-A2
- Card Reader-C1
- imageRUNNER ADVANCE Essentials
- Universal Send Advanced Feature Set-D1
- Super G3 Fax Board-AE1
- Super G3 2nd Line Fax Board-AE1
- Super G3 3rd/4th Line Fax Board-AE1
- Remote Fax Kit-A1
- Barcode Printing Kit-D1
- Web Access Software-H1
- Wireless LAN Board-B1
- USB Device Port-B1
- Multimedia Reader/Writer-A1
- Additional Memory Type B (512MB)
- 2.5-inch/80GB HDD-C1
- 2.5-inch/250GB HDD-D1
- Copy Control Interface Kit-A1
- eCopy Suite
- iR-ADV Security Kit-A1 for IEEE2600.1 Common Criteria Certification†

\* Not available on top cassette.

\*\* Includes consumables.

\*\*\* EPS and XPS cannot be printed directly from Memory Media or Advanced Box.

† Specified configurations and settings need to be applied to the device in order to achieve and maintain IEEE2600.1 Common Criteria Certification. Contact your Canon Authorized Dealer for more information.

NOTE: Some accessories require additional equipment or may be prerequisites for other options. Some accessories cannot be installed simultaneously. Check with your Canon Authorized Dealer for details.

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. PANTONE® and other Pantone, LLC. trademarks are the property of Pantone, LLC. CANON, imageRUNNER, MEAP, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEWARE is a registered trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. Some items may not be available at this time; please check for availability. Specifications and availability subject to change without notice. All printer output images are simulated. Products are shown with optional accessories.

Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance.

©2013 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.



**Canon**  
 image*ANYWARE*

1-800-OK-CANON  
 www.usa.canon.com

Canon U.S.A., Inc.  
 One Canon Park  
 Melville, NY 11747

