

> PRINT > COPY > SCAN > FAX

ECOSYS M4132idn

BLACK AND WITHE MULTIFUNCTIONAL FOR A4/A3 FORMAT

FEATURE RICH PROFESSIONAL OUTPUT



Intuitive 7" full colour touch screen.

Compact design with low-noise printing.













With KYOCERA's unique ECOSYS technology, this new, multifunctional device has been designed for an increased operating life and advanced reliability whilst reducing environmental impact and cutting printing costs. It is a reliable partner for workgroups that require a high level of functionality, easily accessible by touch panel, and represents the smart choice for eco-friendly, cost-conscious offices.



COSYS ECOSYS stands for ECOlogy, ECOnomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. KYOCERA's long-life components cost you and the environment less.

GENERAL

Technology: KYOCERA ECOSYS, Laser, Black and white, HyPAS™ solution platform

Operation panel: 177.8 mm (7 inch) full-colour touch panel display, speaker for job notification

Type: Desktop

Engine speed: Up to 32/17 pages A4/A3 per minute.

Duplex print speed: 29 page per minute, A4
Duplex copy speed: 29 page per minute, A4
Resolution: 1200 x 1200 dpi (print), 600 x 600 dpi

(scan/copy)

Warm-up time: Approx. 2o seconds or less
Time to first print: Approx. 5.2 seconds or less
Time to first copy: Approx. 6.2 seconds or less (DP),
Approx. 5.2 seconds or less (Platen Cover)
CPU: ARM Cortex-Ap Dual core 1.2GHz
Memory: Standard 1GB, max. 3GB
Standard interface: USB 2.0 (Hi-Speed), 2 x USB Host
Interface, Gigabit Ethernet (1oBaseT/10oBaseTX/
1000BaseT), optional Wi-Fi (IEEE 802.11b/g/n), 2 eKUIO
slots, for optional finternal print server or SSD hard disc and
for ontional fax system Slot for optional SD Card NEC tag for optional fax system, Slot for optional SD Card, NFC tag Integrated accounting: 100 department codes Dimensions (WxDxH): 590 x 590 x 688 mm (with standard

Document Processor)

Weight: Approx. 52 kg (with standard Document Processor) Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption Printing: 490 W Copying: 490 W Low power mode: 45 W

Ready mode: 70 W Sleep-mode: 0.5 W Noise (sound pressure level: ISO 7779/ISO 9296)

Copying/Printing: 50 dB (A) Stand-by: 34 dB (A) **Safety standards**: TÜV/GS, CE This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity:

100-sheet multi-purpose tray, 45–256 g/m², A3, A4, A5, A6, B5, Ledger, Letter, Legal, Folio, Custom (98 x 148 to 297 x 432 mm), 500-sheet Standard universal paper cassette, 60–163 g/m², A3, A4, A5, B5, Ledger, Letter, Legal, Folio, Max. input capacity with options: 1,600 sheets

Duplex unit: Duplex as standard supports 60–163 g/m²

**Enadard reversing document processor: 50-sheets, A3, A4,

Standard reversing document processor: 50-sheets, A3, A4, A5, B5, Letter, Legal, Custom (140 x 182 to 297 x 432 mm), Simplex scan 45—160 g/m², Duplex scan 50—120 g/m² Output capacity: Max. 300 sheets; 250 sheets face-down (Main Tray) plus 50 sheets (standard Job Separator Tray)

PRINT FUNCTIONS

Controller language: PRE SCRI BE II e Emulations: PCL6 (5e/XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and Open XPS Operating systems: All current Windows operating systems, MAC OS X Version 10.5 or higher, Unix, Linux as well as other

MAL US X Version 10.5 or rigner, Unix, Linux as well as other operating systems on request
Fonts/barcodes: 101 outline fonts (PCL 6, KPDL 3, Windows
Vista), 1 Bitmap font, 45 types of one-dimensional barcodes,
1 type of two-dimensional barcode (PDF417)

Print features: Encrypted PDF Direct Print, IPP printing,
e-mail printing, WSD print, secure printing via SSL, IPsec,
SNMPy3, quick copy, proof and hold, private print, job
storage and ioh management functionality.

storage and job management functionality

Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google cloud print

COPY FUNCTIONS

Max. original size: A3/Ledger Continuous copying: 1–999
Zoom range: 25–400% in 1% steps
Preset magnification ratios: 5 Reductions / 5 Enlargements

Exposure mode: Auto, manual: 7 steps

age adjustments: Text + Photo, Photo, Text, Map, Printed document

Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change (PF-470 or PF-471 is required), copy density control, Prevent Bleed-Through, ID card copy, Skip blank page

Functionality: Scan-to-Email, Scan-to-FTP, Scan-to-SMB, Scan to USB Host, Network TWAIN, WIA , WSD scan Scan speed: 50 ipm (300 dpi, A4, black and white), 50 ipm (300 dpi, A4 colour)

Scan resolution: 600, 400, 300, 200 dpi (256 greyscales

Max. scan size: A3, Ledger

Original recognition: Text, photo, text + photo, light text, optimised for OCR File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted

PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u

Compression method: MMR/JPEG Features: Colour scan, integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once, Blank page skip

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU -T Super G3 Modem speed: Max. 33.6 kbps Transmission speed: Max. 33.6 kbps Scanning speed: 2.0 seconds or less Address book: 200 entries Scanning density: Normal: 8 dot/mm x 3.85 line/mm (200 x 100 dpi)

Fine: 8 dot/mm x 7.7 line/mm (200 x 200 dpi)
Superfine: 8 dot/mm x 15.4 line/mm (200 x 400 dpi)
Ultrafine: 16 dot/mm x 15.4 line/mm (400 x 400 dpi) Halftone: 256 grey scales

Maximum original size: A3, Ledger Compression method: IBIG, MMR, MR, MH Memory reception: 700 sheets or more Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

CONSUMABLES

Average continuous toner yield in accordance with

ISO/IEC 19752
TK-6115 Toner Kit: Microfine toner black for 15,000 pages A4
Capacity of starter toner is 3,000 pages A4
Staple: SH-10,5000 x 3 staples

OPTIONS

Fax System 13 Paper handling

Paper handling
PF-470 Paper feeder: Max. 500 sheets; 60–163 g/m²; A3,
A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm)
PF-471 Paper feeder: Max. 1,000 sheets; 60–163 g/m²; A3,
A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm)
DF-470* Paper feeder: Document finisher with AK-470,
Max. 500 sheets A4; 60–163 g/m²; A3, A4, A5, B5, Letter,
Legal (Lustom (98 x 148 to 207 x 62 mm) 2 positions Legal, Custom (98 x 148 to 297 x 432 mm), 3 positions stapling up to 50 sheets A4 or 25 sheets A3 *Bridge unit AK-470 is required for the use of DF-470 **Security**: Data security kit (E):

Memory upgrade: DDR3 1GB/2GB
HD-6: SSD 32 GB for easy document management
HD-7: SSD 128 GB for easy document management

SD card: for printing forms, fonts, logos, macro storage and for HyPASTM applications USB Flash Memory: Supports direct printing and scanning of PDF, XPS, TI FF, JPEG files via USB Host interface

USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available. The card holder is standard

Optional interface

IB-36: Wireless LAN (802.11b/g/n) with Wi-Fi Direct

IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/ 1.000 BaseT

IB-51: Wireless LAN Interface (802.11b/g/n)
CB-470 Cabinet: Wooden desk with storage capacity, including castors (wheels)

CB-471 Base Unit: Wooden base for height increase (to be used only with PF-470 or PF-471)
CB-472 Cabinet: Metal desk with storage capacity,

including castors (wheels) **CB-473 Base Unit:** Metal base for height increase (to be used only with PF-470 or PF-471)

WARRANTY

2-year warranty as standard.** KYOCERA guarantees the drum and developer for 3 years or 300,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.



Up to 5-year on-site warranty extensions available for product and options.















Tel: 0118 931 1500, Fax: 0118 931 1108 www.kyoceradocumentsolutions.co.uk, info@duk.kyocera.com

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



^{**} Depending on the country