imageRUNNER ADVANCE 6575i/6565i/6555i/6555i PRT

High quality, efficient and dependable

The imageRUNNER ADVANCE 6500 Series delivers high performance and quality black-and-white output for demanding office environments. These intelligent multifunctionals* enhance productivity through improved document workflows and an intuitive user experience.



Streamline document workflows


- Intuitive user interface with a large, responsive colour touchscreen with smart phone-like usability.
- Effortless, rapid scanning captures paper-based documents with ease.*
- Advanced personalisation enables a unique, personal experience tailored to meet each user's workflow needs.
- Canon's MEAP platform provides process optimisation, by integrating with a range of powerful document, capture* and output management solutions.
- Scalable support for mobile and flexible working styles allows workers to capture* or print documents and access certain cloud applications on the go.
- Scan and convert documents to Searchable PDF, Microsoft® Word, and Microsoft® PowerPoint files through a single-pass duplexing document feeder® that holds up to 300 originals.
- Motion sensor technology wakes device from sleep mode.
- Automatically remove blank pages when scanning*.
- Users can create professional-looking booklets and finished documents automatically.
- Convenient Staple-on-demand functionality.

Control Costs

- Technology designed to reduce total cost of print.
- Apply print policies, monitor output, and restrict usage by user.
- Tight integration with output management solutions, such as uniFLOW.
- Remote diagnostics and assistance, help reduce costs by minimising downtime and time spent by IT resolving issues.
- Remote and centralised fleet management simplifies IT management of devices and fleets.
- Options for cost recovery and coin vending integration.

Secure confidential information

- Control who has access to the device with Award-winning, smart user authentication without impacting on user productivity or convenience.
- Prevent unauthorised distribution of sensitive information with an array of standard and optional document security features.
- Ensure information privacy and security across your network with IPsec, port filtering capabilities, and SSL technology.
- Secure Print and Mailbox enhance document confidentiality.
- Ability to disable functions by user to prevent unauthorised usage.
- Industry-first Data Loss Prevention and auditing of prints, copies, scans and faxes through uniFLOW.















Manage devices efficiently

- Pre-configure devices making installation easy.
- Simplified fleet management by synchronising settings across multiple devices.
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices, check device status and consumables, turn off devices remotely, capture meter readings, as well as manage address books and printer drivers.
- Supports industry network standards i.e. PCL and Adobe PostScript for seamless integration.
- Shares resources and functionality with other imageRUNNER ADVANCE devices on the network.
- Collaborates with business applications and external systems in the Cloud.
- Remote diagnostics allow preventive maintenance.

Reliable results

- Canon's signature reliability and engine technologies provide high quality output to meet the needs of busy departments.
- State-of-the-art imaging technologies and toner allow for consistently striking images in rich black-and-white tones and 1,200 dpi. print resolution.
- Designed to achieve maximum uptime with intuitive user maintenance videos and status notifications, to help keep supplies replenished.

Environmentally responsible

- Fusing technologies, pO toner, and innovative sleep mode features help lower overall energy consumption.
- Minimise waste with default 2-sided printing, secure printing, and the ability to hold print jobs, preview them and change print settings at the device, achieving the desired results at the first time of printing.
- Incorporates sustainable design, with the use of recycled materials and bio-based plastic, and a focus on minimising environmental impact.
- ENERGY STAR® qualified.
- Reduce waste with Staple-less Eco stapler.
- Consumes as little as 0.9 in sleep mode.
- Class leading Typical Electricity Consumption (TEC*) ratings.

Configuration



STAPLE FINISHER-V1

- 3-tray, 3,500 -sheet capacity
- Corner and double stapling up to 65 sheets (80gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On Demand 65 sheets (80 gsm)
- Supports optional internal 2/4 and 4 hole inner punchers - (2/4 Hole Puncher Unit-A1 and 4 Hole Puncher Unit-A1)



BOOKLET FINISHER-V1

- 3-tray, 3,500 -sheet capacity
- Corner and double stapling up to 65 sheets (80 gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/A4R)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On Demand 65 sheets (80 gsm)
- Supports optional internal 2/4 and 4 hole inner punchers - (2/4 Hole Puncher Unit-A1 and 4 Hole Puncher Unit-A1)



DOCUMENT INSERTION/

- Insert pre-printed sheets
- Up to A3
- 1-tray, 100-sheet capacity
- Z-fold, C-fold



DOCUMENT INSERTION UNIT-P1

- Insert pre-printed sheets
- Up to A3
- 1-tray, 100-sheet capacity





imagePASS-Y1

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Personalised printing with the built-in, entry-level Fiery FreeForm (TM) or with the supported industry-leading variable data printing (VDP) formats
- Integrates print production workflows with EFI (TM) management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation
- Communicates with the full suite of optional uniFLOW modules



Technical Specifications

imageRUNNER ADVANCE 6575i/6565i/6555i/6555i PRT

Main Unit

Machine type Core functions **Processor Speed** Control Panel Hard Disk drive

Paper input (Standard) Paper input (Option)

Maximum paper input

Paper output capacity

Finishing capabilities

Supported media types

Supported media sizes

Supported media weights

Warm-up Time

Dimensions (W x D x H) Installation Space(W x D x H)

Print Specifications

Printing method **Print Speed**

Print Resolution Page description languages

Monochrome Laser Multifunctional Printer Print, Copy¹, Scan¹, Send¹, Store and Optional Fax¹ Canon Dual Custom Processor (Shared)

10.1 inch TFT LCD WSVGA Colour Touchpanel Standard: 3.0GB RAM

Standard: 250GB Maximum: 1TB

Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) Optional: NFC

Others

Others Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device) Optional: Serial Interface,Copy Control Interface

7,700 sheets (80gsm)

With Copy Tray: 250 sheets (80gsm) With External Finishers: Max. 3,500 sheets (A4). With Shift Tray: 500-sheets (A4, 80gsm)

<u>Lower Cassettes (3/4):</u> Thin paper, Plain paper, Recycled paper, Colour paper, Heavy

paper, Pre-punched paper, Bond, Transparency, Labels, Letterhead, Tab paper, Tracing²

paper, Pre-punched paper, Letterhead, Bond paper

<u>Upper Left/Right Cassettes(1/2):</u> Standard size: A4, B5

<u>Lower Cassettes (3/4):</u> Standard size: A3, A4, A4R, A5R, B5, B5R Custom size: 139.7 mm x 182 mm to 297 mm x 431.8 mm

<u>Multi-purpose tray:</u> Standard size: A4, A4R, A3, A5R, B5, B5R Custom size: 100 mm x 148 mm to 297 mm x 431.8 mm Free size: 100 mm x 182.2 mm to 297 mm x 431.8 mm

POD DECK UNIT-C1: A3, A4, A4R, A5R, and Custom Size (139.7 mm x 182 mm to 297 x 431.8 mm)

PAPER DECK UNIT-E1:

Cassettes: 52 to 220 gsm Multi-purpose tray: 52 to 256 gsm Duplex: 52 to 220 gsm

From Power On: 30 Seconds or Less From Sleep Mode: 30 Seconds or Less Quick Startup Mode: 4 Seconds³ 670 mm x 779 mm x 1.220 mm

1.362 mm x 1.353 mm (Basic: Only Multi-purpose tray + Cassette drawers open + Copy Tray)

 $2,407\,mm\,x\,1,353\,mm$ (Fully configured: Includes Booklet finisher + A3 Paper Deck + Insertion and folding unit + Puncher unit + Cassette drawers open)

Approx. 234kg⁴

Monochrome laser beam printing

<u>iR-ADV 6555i/6555i PRT</u> 32 ppm (A3) 55 ppm (A4) 40 ppm (A4-R) 35 ppm (A5R)

<u>iR-ADV 6565i:</u> 32 ppm (A3) 65 ppm (A4) 47 ppm (A4-R) 35 ppm (A5R) iR-ADV 6575i: 37 ppm (A3) 75 ppm (A4) 54 ppm (A4-R) 35 ppm (A5R)

UFR II, PCL 5e/6 (standard) Genuine Adobe PostScript Level 3 (Option)

1,200 dpi x 1,200 dpi, 600 dpi x 600 dpi

Double Sided Printing

Direct Print

Printing from mobile and

Fonts

Operating System

1,500 sheets x 2 Sheet cassettes + 550 sheets cassettes x 2 cassettes (80gsm) 100 sheets Multi-purpose tray(80gsm)

Additional 3,500 sheets (POD DECK LITE-C1 or PAPER DECK UNIT-E1)

Collate, Group, Offset. With External finisher: Staple, Saddle Stitch, Hole Punch, Insertion, C & Z folding

Upper Left/Right Cassettes(1/2): Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Letterhead, Bond paper

paper, Pre-punched paper, Letterhead, Bond paper, Tab paper'. "Tab paper can be fed from both cassette 3 & 4 when the optional TAB FEEDING ATTACHMENT KIT-B1 is installed.

<u>Multi-purpose tray:</u> Thin paper, Plain paper, Recycled paper, Colour paper, Heavy

POD DECK LITE-CI: Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Letterhead, Bond paper, Transparency, Labels, Tab paper

PAPER DECK UNIT-E1: Thin paper, Plain paper, Recycled paper, Colour paper, Heavy

Scan Specifications Standard type

Supported media size/s Supported media weight/s

Pull Scan Spec

Scan Resolution Acceptable Originals

Scan Method

Scan Speed (BW/Colour: A4)

Paper Capacity Double sided scanning

Optional / Standard Destination Address Book Send resolution

Automatic (Standard)

Direct printing available from USB memory key, Advanced space, Remote UI and Web Access

Supported file types: TIFF, JPEG, PDF and XPS,

A range of software and MEAP-based solutions is available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T* (Japanese, Korean, Simplified and Traditional Chinese)* "Requires optional PCL INTERNATIONAL FONT SET-A1.

PS fonts: 136 Roman

UFRII: Server 2003/Server 2003 R2Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012//Windows 8.1/Server 2012 R2/Windows 10, MAC OS X (10.5.8 or later)

PCL: Server 2003/Server 2003 R2Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012//Windows 8.1/Server 2012 R2/Windows 10

PS: Server 2003/Server 2003 R2Vista/Server 2008/Windows 7/ Server 2008 R2/Windows 8/Server 2012//Windows 8.1/Server 2012 R2/Windows 10, MAC OS X (10.5.8 or later)

PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows Vista/Windows 7/Windows 8/Windows 8.1/Windows10

SAP Device Types are available via the SAP Market Place. Please refer to http://software.canon-europe.com/ for availability of print solutions for other operating systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable.

iR-ADV 6555i: 32 ppm (A3), 55ppm (A4), 40 ppm (A4R), 35 ppm (A5R) iR-ADV 6565i: 32 ppm (A3), 65 ppm (A4), 47 ppm (A4R),

Copy Speed

35 ppm (A5R) iR-ADV 6575i: 37 ppm (A3), 75 ppm (A4), 54 ppm (A4R), 35 ppm (A5R) First-Copy-Out Time

iR-ADV 6555i: Approx. 3.3 seconds or less iR-ADV 6565i: Approx. 3.3 seconds or less iR-ADV 6575i: Approx. 3.1 seconds or less Reading: 600 dpi x 600 dpi Printing: 1,200 dpi x 1,200 dpi Copy resolution

Up to 9,999 copies **Multiple Copies** Magnification 25% - 400% (1% Increments) Preset Reductions 25%, 50%, 64%, 73%, 78% Preset Enlargements

121%, 129%, 200%, 400%

A3, A4, A4R, A5, A5R

Colour flatbed scan unit plus 300-sheet duplex automatic document feeder (1-Pass duplex Colour scan).

Single-sided scanning: 38 to 220 gsm (BW) Single-sided scanning: 64 to 220 gsm (CL) Double-sided scanning: 50 to 220 gsm (BW) Double-sided scanning: 64 to 220 gsm (CL)

Colour Network ScanGear2. For both Twain and WIA

Supported OS: Windows Vista/7/8/8.1/10 Windows Server 2003/Server 2003 R2/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2 100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi Platen: Sheet, Book, 3-Dimensional Objects (Up to 2kg)

Feeder size: A3 A4 A4R A5 A5R

Feeder weight Single-sided scanning: 38 to 220 gsm (BW) Single-sided scanning: 64 to 220 gsm (CL) Double-sided scanning: 50 to 220 gsm (BW) Double-sided scanning: 64 to 220 gsm (CL)

Send functionality available on all models

Scan to USB Memory Key: Available on all models Scan to Mobiles or internet-connected devices: A range of scan to Mobiles on Internet-commerced devices. A range of solutions is available to provide scanning to mobile devices or internet-connected devices depending on your requirements. Please contact your sales representative for further information.

Scan to cloud-based services: A range of solutions is available to provide scanning to cloud-based services depending on your requirements. Please contact your sales representative for further information.

TWAIN/WIA Pull scanning available on all models Single-sided (A4, 300 dpi): 120/120 ipm (BW/CL); Single-sided (A4, 600 dpi): 120/60 ipm (BW/CL); Double-sided (A4, 300dpi): 240/220 ipm (BW/CL) Double-sided (A4, 600 dpi) 150/60 ipm (BW/CL)

300 Sheets (80 gsm) 2-sided to 2-sided (Automatic)

Standard on all models

E-mail/Internet FAX (SMTP), SMB, FTP, WebDAV LDAP (2,000)/Local (1,600)/Speed dial (200) 100×100 dpi, 150×150 dpi, 200×100 dpi, 200×200 dpi, 200×400 dpi, 300×300 dpi, 400×400 dpi, 600×600 dpi



Technical Specifications

imageRUNNER ADVANCE 6575i/6565i/6555i/6555i PRT

Communication protocol

File: FTP. SMB . WebDAV

E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply PDF file protection by Adobe Live Cycle Rights Management¹⁸, Optimis for Web, PDF A/1-b), XPS (Compact, Searchable), Office Open XML (PowerPoint, Word)

Optional: PDF (Trace&Smooth, Encrypted), PDF/XPS (Digital

Signature)

Original Type Selection,Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Select Line, Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed.

Fax Specifications¹

Universal Send Features

Optional / Standard

Modem Speed Compression Method

Resolution

Sending/Recording Size

FAX memory Speed dials

Group dials/destinations Sequential broadcast

Memory backup Fax Features

Max. 199 dials

Store Specifications

Advanced Space Features

Memory Media

Authentication

Data

Network

Document

Environmental Specifications

Operating Environment

Power source

Optional on all models

Super G3 33.6 kbps (Up to 3 seconds per page⁶)

MH, MR, MMR, JBIG

400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi

A5 and A5R* to A3 Sent as A4

Up to 6,000 pages⁶ Max. 200

Max. 256 addresses

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed.

Disabling Advanced space, Storage Filtering, Authentication for Advanced space Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager

Standard: USB Memory

Standard: Universal Login Manager (Device and Function Level Log-in), User Authentication, Department ID, Authentication, Access Management System

Optional: My Print Anywhere secure print (Requires uniFLOW)

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated)
Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, Data Loss Prevention (Requires uniFLOW)

Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP

Standard: Secure Print, Adobe LiveCycle® Rights Management

Optional: Encrypted PDF, Encrypted Secure Print, User and Device signatures, Secure Watermarks, Document Scan locking

Temperature: 10 to 30 °C (50 to 86 °F) Humidity: 20 to 80% RH (no condensation) 220-240V(±10%), 50/60Hz (±2 Hz), 10Amp Power consumption

Maximum: Approx. 2.4 KW Maximum: Approx. 2.4 KW Standby: Approx. 238 Wh Energy Saver Mode: Approx. 237 Wh Sleep mode: Approx. 0.9 W or less' Typical Electricity Consumption (TEC) rating®: 4.9 kWh (iR-ADV 6555)/6555i PRT) 6.1 kWh (iR-ADV 6565) 6.7 kWh (iR-ADV 6565)

Noise levels

Sound Pressure⁹ Active: 75 dB or Less Standby: 58 dB or Less

Consumables

Toner Cartridge/s

Toner (Estimated Yield @6%

C-EXV 36 TONER BK 56,000 pages

Hardware Accessories

Card Readers: MICARDPLUS FOR ULM, CARD READER-F1, COPY CARD READER ATTACHMENT-A3

Others: TAB FEEDING ATTACHMENT KIT-B1, STAMP INK CRG-C1, UTILITY TRAY-B1

Security Options:

DOCUMENT SCAN LOCK KIT-B1, SECURE WATERMARK-B1, ENCRYPTED SECURE PRINT SOFTWARE-D1

HDD MIRRORING KIT-J1, 2.5INCH/250GB HDD-N1, 2.5INCH/1TB HDD-P1, REMOVABLE HDD KIT-AL1

System and Controller options:

PCL INTERNATIONAL FONT SET-A1, PS PRINTER KIT-BC1

Send options.
UNIVERSAL SEND SECURITY FEATURE SET-D1, UNIVERSAL SEND DIGITAL USER SIGNATURE KIT-C1, UNIVERSAL SEND TRACE & SMOOTH PDF KIT-A1

Barcode printing: BARCODE PRINTING KIT-D1

EFI-Fiery based controller: IMAGEPASS-Y1, REMOVABLE HARD DISK DRIVE KIT-B4

EFI-Fiery based controller options: FIERY IMPOSE,FIERY COMPOSE, FIERY IMPOSE AND COMPOSE

System accessories: WEB ACCESS SOFTWARE-J2, SERIAL INTERFACE KIT-K2, NFC CONTROL PANEL-B1

FAX accessories: SUPER G3 FAX BOARD-AS1, SUPER G3 2ND LINE FAX BOARD-AS1, REMOTE FAX KIT-A1, IP FAX EXPANSION KIT-B1

Other Options:

Accessibility accessories: ADF ACCESS HANDLE-A1, VOICE GUIDANCE KIT-G1, VOICE OPERATION KIT-D1

Staple Cartridge: STAPLE CARTRIDGE-X1, STAPLE CARTRIDGE-Y1

Not available on 6555i PRT

[2] Some types of tracing paper cannot be used.

 $^{(3)}$ The time until key operations can be performed on the touch panel display is 3 seconds or less.

[4] Including the toner bottle

[5] PDF print only from websites

[6] Based on ITU-T Standard Chart No. 1

 $^{(7)}$ 0.9 watt sleep mode may not be possible in all circumstances. Certain network configurations and options may prevent the device from entering deep sleep mode. Please refer to the user guide for more information

[8] Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh). The test methodology is defined by Energy Star (http://www.eu-energystar.org).

[9] Declared noise emission in accordance with ISO 7779

† Refer to local Canon web site

For full information on options available for the iR-ADV 6500 series, please refer to the specification tables on your local Canon web site.

Software and Solutions

























Certifications and compatibility



















Canon Inc. canon.com

Canon Europe canon-europe.com

English edition © Canon Europa N.V. 2016 Canon (UK) Ltd Woodhatch Reigate Surrey RH2 8BF Telephone no 01737 220000

canon.co.uk

Facsimile 01737 220022

Canon Ireland 3006 Lake Drive Citywest, Saggart Co.Dublin, Ireland Telephone No: 01 2052400 Facsimile No: 01 2052525

canon.ie

