

Compact workgroup productivity.

imageRUNNER
2520/i, 2525/i, 2530/i,
2535/i, 2545/i

you can

A RANGE OF SPEEDS FROM 20 TO
45 PPM / CPM, A3 BLACK-AND-WHITE

UP TO 2,300 SHEET PAPER CAPACITY

SEND DIRECT TO EMAIL AND
NETWORK FOLDER

5.7 INCH / 14.47 CM TOUCH
SCREEN DISPLAY

CLASS-LEADING ENERGY EFFICIENCY

COMPACT DESIGN

Productivity and efficiency

- Easy-to-use touch-screen display saves time
- Fast output speeds up to 45 ppm
- Send in colour to network folders or email in a variety of formats*
- Fewer interruptions with up to 2,300 sheet paper capacity
- Simple, hassle-free integration – Network ready, PCL* and optional PostScript Support
- Optional inner staple finisher
- e-Maintenance service provides remote diagnostics, automated meter readings and toner management.

Ideal for busy, small and medium workgroups, this versatile range provides for everyday black-and-white printing, copying, colour scanning and advanced send direct to email and network folder. With a variety of speeds up to 45 ppm, excellent responsiveness and energy efficiency these devices will save you time, money and energy.



Environmental

- Exceptional energy efficiency – as little as 1.5 watts power consumption in sleep mode, saves energy and cost
- Save paper – automatic double-sided output.

Cost-effective

- Low cost of ownership
- Enhanced productivity and class-leading energy efficiency maximises value
- Compatibility with uniFLOW solution offers Cost Centre selection and reporting for cost control and monitoring
- Accurate billing through e-Maintenance.

Security

- Secure Print** keeps documents confidential during printing
- Department ID secures access to the device
- uniFLOW compatibility offers the flexibility and convenience of My Print Anywhere secure release with job selection.

* Standard on i models, optional on non i models
** RAM-based secure print for up to 100 jobs

imageRUNNER

Canon

Specifications: imageRUNNER 2500 Series

Type Maximum Original Size Copy Sizes	Desktop or Free-standing (Reader-Printer Combined) A3 Cassette 1, 3, 4 A3, A4, A4R, A5R Custom size: 139.7 to 297mm x 182 to 432mm	
Resolution	Stack Bypass Custom Size Reading Copying Printing No. of Tones	A3, A4, A4R, A5R 99 to 297mm x 148 to 432mm 600dpi x 600dpi 600dpi x 600dpi 600dpi x 600dpi, 1200dpi x 1200dpi (UFRII-LT only) 256 Gradients
COPY/PRINT SPEED		
	A4	imageRUNNER 2545i / 2545: 45ppm (BW) imageRUNNER 2535i / 2535: 35ppm (BW) imageRUNNER 2530i / 2530: 30ppm (BW) imageRUNNER 2525i / 2525: 25ppm (BW) imageRUNNER 2520i / 2520: 20ppm (BW)
	A3	imageRUNNER 2545i / 2545: 22ppm (BW) imageRUNNER 2535i / 2535: 22ppm (BW) imageRUNNER 2530i / 2530: 15ppm (BW) imageRUNNER 2525i / 2525: 15ppm (BW) imageRUNNER 2520i / 2520: 15ppm (BW)
Magnification First Copy Time	Zoom Black & White	25-400%; Fixed: 25%, 50%, 70%, 100%, 141%, 200%, 400% 3.9 sec (45 / 35ppm model), 5.4 sec (30 / 25ppm model), 6.4 sec (20ppm model)
Warm-Up Time Multiple Copies/Prints	Duplexing	30 seconds 1 to 999 sheets
Paper Weight	Cassette	Standard 64 to 90g/m ² ; Stack Bypass: 64 to 128g/m ² ; Duplex: 64 to 80g/m ²
Paper Capacity	Cassette 1	550 sheets (80g/m ²) (250 sheets for the imageRUNNER 2520i / 2520)
	Cassette 2 Stack Bypass Optional	550 sheets for imageRUNNER 2525i/i, 2530/i, 2535/i, 2545/i 100 sheets (A4, A4R, A5: 80g/m ²), 50 sheets (A3: 80g/m ²) 550 sheets x 2 cassettes (80g/m ²) 550 sheets x 1 cassette for imageRUNNER 2520 / 2520i only
	Paper Deck Total Capacity	None 2,300 sheets, (2,000 sheets for the imageRUNNER 2520i / 2520) Canon Custom Processor, 400MHz 512MB (imageRUNNER 2500 i models), 256MB (imageRUNNER 2500 non i models)
CPU Memory	Hard Disk Drive Interface	None Ethernet (100Base-TX / 10Base-T), USB Host I / F 2.0 x 1 port, USB Device 1.0 x 1 port
Power Supply		220-240V AC, 50/60Hz, 4.2A (45 / 35ppm model), 220-240V AC, 50/60Hz, 3.3A (30 / 25 / 20ppm model)
Max. Power Consumption		1.827kW (45 / 35ppm model), 1.345kW (30 / 25ppm), 1.542kW (20ppm model)
Dimensions (W x D x H)		imageRUNNER 2545i / 2545 / 2535i / 2535 565 x 680 x 806mm (with the platen cover), 565 x 689 x 907mm (with the DADF) imageRUNNER 2530i / 2530 / 2525i / 2525 565 x 680 x 806mm (with the platen cover), 565 x 689 x 896mm (with the DADF) imageRUNNER 2520i / 2520 565 x 680 x 681mm (with the platen cover), 565 x 689 x 771mm (with the DADF)
Weight		imageRUNNER 2545i / 2535i: Approx. 78.4kg, imageRUNNER 2545 / 2535: Approx. 70.5kg, imageRUNNER 2530i / 2525i: Approx. 77.5kg, imageRUNNER 2530 / 2525: Approx. 68.0kg, imageRUNNER 2520i: Approx. 56.0kg, imageRUNNER 2520: Approx. 50.5kg
PRINT SPECIFICATION		
PDL		UFRII-LT, PCL5e/6 (standard on i models, optional on non i models), PostScript level 3 emulation (optional)
Resolution		600 x 600dpi, 1200dpi x 1200dpi (UFRII-LT only)
Memory		512MB (imageRUNNER 2500 i models), 256MB (imageRUNNER 2500 non i models)
Hard Disk		None
CPU		Canon Custom Processor, 400MHz
Fonts		PS Fonts: Roman 136, PCL Fonts: Roman 93
Supported OS		PCL: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7, Postscript level 3 emulation: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7, Mac OS X (10.4 or later) UFRII-LT: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7, Mac OS X (10.4 or later), Linux Mac-PPD: Mac OS X 10.4 or later
Interface		Ethernet (100Base-TX / 10Base-T)
Network Protocol		TCP / IP (LPD / Port9100, HTTP), SMB, SNMPv1, WSD, IPv4 / IPv6 support
Pull Scan		Network TWAIN Driver (75 / 100 / 150 / 200 / 300dpi 8bit colour / 75-600dpi 1bit Black-and-White)
SEND SPECIFICATION/ CLR SEND KIT-Y1		
(standard on i models, optional on non i models) Scan Speed (A4, 300dpi, BW/Colour) Scan Resolution	BW	45 / 34ipm (45 / 35ppm model), 25 / 13ipm (30 / 25 / 20ppm model) 100 x 100dpi, 150 x 150dpi, 200 x 100dpi, 200 x 200dpi, 200 x 400dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi
	CL	100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 300 x 300dpi E-Mail / Internet FAX (SMTP), PC / Server (SMB,FTP), USB memory keys Local (Max. 500) TIFF, JPEG, PDF, High compression PDF, Searchable PDF (optional with Searchable PDF-C1)
Destinations Address Book File Format		

DADF-AA1 for imageRUNNER 2545/2535		
Paper Size Paper Weight		A3, A4, A4R, A5, A5R Single sided original: 42 to 128g/m ² , Double sided original: 50 to 128g/m ² 100 sheets (A4, A4R, A5, A5R: 80g/m ²), 50 sheets (A3: 80g/m ²)
Max. Number of Originals Document Scanning Speed (max.)	Copy Scan	45ipm (A4, 600 x 600dpi: BW) 45 / 34ipm (A4, 600 x 600dpi: BW / 300 x 300dpi: Colour) 565 x 540 x 137mm Approx. 7.9kg
Dimensions (W x D x H) Weight		
DADF-AB1 for imageRUNNER 2530/2525/2520		
Paper Size Paper Weight		A3, A4, A4R, A5, A5R Single sided original: 37 to 128g/m ² , Double sided original: 50 to 128g/m ² 50 sheets (A4, A4R, A5, A5R: 80g/m ²), 25 sheets (A3: 80g/m ²)
Max. Number of Originals Document Scanning Speed (max.)	Copy Scan	25ipm (A4, 600 x 600dpi: BW) 25 / 13ipm (A4, 600 x 600dpi: BW / 300 x 300dpi: Colour) 565 x 544 x 126mm Approx. 7.0kg
Dimensions (W x D x H) Weight		
CASSETTE UNIT-W1 for imageRUNNER 2520/i		
Type Paper Size Custom Size Paper Weight Paper Capacity Dimensions (W x D x H) Weight		Front-loading adjustable drawers A3, A4, A4R, A5R 139.7 to 297mm x 182 to 432mm 64 to 90g/m ² 550 sheets (80g/m ²) x 1 cassette 565 x 680 x 97mm Approx. 12.8kg
CST. FEEDING UNIT-AE1 for all models		
Type Paper Size Custom Size Paper Weight Paper Capacity Dimensions (W x D x H) Weight		2 Front-loading adjustable drawers A3, A4, A4R, A5R 139.7 to 297mm x 182 to 432mm 64 to 90g/m ² 550 sheets (80g/m ²) x 2 cassettes 565 x 680 x 248mm Approx. 24.0kg
INNER FINISHER-B1 for all models		
Number of Trays Tray Capacity		One stack tray (Optional 2nd Tray: INNER FIN ADD. TRAY-B1) A4, A5, A5R: 1,000 sheets (or 125mm in height) A3, A4R: 500 sheets (or 62.5mm in height) Corner, Double
Staple Position Staple Capacity Dimensions (W x D x H) Weight		A4: 50 sheets x 30 sets; A4R / A3: 30 sheets x 15 sets 416 x 554 x 350mm, 703 x 554 x 350mm (with output tray extended) Approx. 12.5kg
INNER 2-WAY TRAY-G1 for all models		
Number of Trays Tray Capacity	Tray A Tray B	2 stack tray A4: 250 sheets, A3: 100 sheets A4: 100 sheets, A3: 50 sheets 426 x 413 x 109mm Approx. 0.6kg
Dimensions (W x D x H) Weight		
OTHER ACCESSORIES		
Platen Cover Type P: for imageRUNNER 2525/2530 without DADF Platen Cover Type Q: for imageRUNNER 2535/2545 without DADF Stamp Ink Cartridge-C1 Stamp Unit-B ADF Access Handle-A1 PCL Printer Kit-AF1: Supports PCL5e and PCL6 printing for non-i Models PS Printer Kit-AF1: Supports PostScript Level 3 Emulation printing. Barcode Printing Kit-B1: Provides Barcode printing capability using Jet Caps technology Super G3 Fax Board-AG1: Add fax functionality FL Cassette-A11: This spare 550-sheet tray for cassette '1' of imageRUNNER 2525 / 2525i / 2530 / 3530i / 2535 / 2535i / 2545 / 2545i FL Cassette-AK1: This spare 550-sheet tray for cassette '2' of imageRUNNER 2525 / 2525i / 2530 / 3530i / 2535 / 2535i / 2545 / 2545i or for Cassette Feeding Unit-AE1 or Cassette Module-W1 FL Cassette-AL1: This spare 250-sheet tray for cassette '1' of imageRUNNER 2520 / 2520i allows you to swap paper sizes without changing the printer settings. Cassette Spacer-A1: Adjusts the height for 250-sheet cassette when combined with optional Cassette Feeding Unit-AE1 or Cassette Module-W1 on imageRUNNER 2520 / 2520i only. 2 Way Unit-B1: Enhances the double-sided print productivity up to 100% Reversal Pass Unit (2-Way Unit) option for imageRUNNER 2520 / 2520i / 2525 / 2530. Staple-J1: Staples for Inner Finisher-B1. Document Tray-J1: Handy tray that attaches to the side of the device. Power Supply Unit-U1. Card Reader Attachment-D3: Attachment kit for Card Reader-F1. Canon Card Reader-F1: Physical card access system that limits system access to authorised users. USB Application 3-Port Interface Kit-A1: 3-Port USB interface kit for USB memory. CCVI I/F Cable-A1: Interface Kit for Coin-Vender. C-EXV33 TONER BK: Toner for imageRUNNER 2520 / 2520i / 2525 / 2525i / 2530 / 2530i. C-EXV32 TONER BK: Toner for imageRUNNER 2535 / 2535i / 2545 / 2545i		
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.		

Canon



Canon Inc.
canon.com

Canon Europe
canon-europe.com

English Edition 0163W635
01/12/v1
© Canon Europa N.V., 2012

Canon (UK) Ltd
Woodhatch
Reigate
Surrey
RH2 8BF
Tel.: 01737 220000
Fax: 01737 220022
canon.co.uk

Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Tel.: 01 2052400
Fax: 01 2052525
canon.ie